

Alabaster Sheets | Charcoal Panels | Viga Planks
Estilo Backlit Panels | Acrilico | PETG Sheets | Elite Panels

ACRILICO
THE GLASS LAMINATE

www.theultimo.in | royaltradelinks55@gmail.com

Copyright © 2020 (ULTIMO)- All rights reserved 1.ULTIMO expressly disclaims any representation or warranties of any kind, whether express or implied, as to the accuracy, currency, completeness and/or the merchantability or fitness for a particular purpose of any information contained in or provided via this documentation and/or any service or product described or promoted in this document. 2. It is the customers responsibility to throughly examine the product by a qualified person, to determine whether it is suitable for the application it was purchased for. 3.ULTIMO acrylic is for indoor use only and should not be exposed to direct sunlight in any form.4.ULTIMO is a registered trademark.5. Images and colours should be used as guide only 6. ULTIMO warrants that its products are free from manufacturing defects and they are suitable for use under normal conditions. Product must be inspected prior to installation. In case of any claims, The liability of the company is limited to the cost of the product only. 7. Decorative acrylic sheets are translucent in nature and should be pasted on plain side of calibrated surface. 8. Use suitable adhesive for pasting these sheets 9. The information provided on this sheet represents typical properties and does not constitute a specification. No liability will be accepted for errors and omissions. ULTIMO also retains the right to change sizes and specifications of the products without prior notice.







The Un-beatable Gloss

ULTIMO `Acrillco' is a range of acrylic with high gloss finish which is strongly resistant to micro scratches and abrasions. High resistance is the ability of a surface to resist permanent deformation/micro-scratches resulting from the application of a dynamic mechanical force. An unbeatable match of highly-reflective surface and toughest resistance to damage gives you the liberty to handle acrylic carefree.

`Acrillco' is crafted for a high aesthetic appeal with sturdiness. This makes it suitable for tough use without compromising on beauty.

ULTIMO `Acrilico' 6H Scratch resistant is a uniquely engineered product that incorporates the benefit of a thinner competitively priced product with a more durable impact resistant material. Our 6H superior scratch and impact resistant acrylic allows for one product to take the place of two by allowing the designer to use 1.5/2mm acrylic in kitchens and bedrooms even in the most abusive and high impact areas. `Acrilico' scratch resistant acrylic is answer for all your design and application requirements.

Acrylic is a proven performer because it has a single infused acrylic core into one layer. This means: The colour is not a thin, inconsistent or patchy layer of paint. The colour layer is fused to the clear acrylic and will not separate easily. Unlike glass and other painted acrylic sheet products, minor scratches to the colour layer will not show through.















Home Décor Furniture

Commercial Interior Furniture

Kitchen Cabinets

Healthcare Furniture

→ Wall Panels/Partition & many more





1.5MM & 2MM





UA-1201 | 2201 Snow White

UA-1205 | 2205 Pearl White **UA-1207|2207** Champagne

























Warnings:

Acrylic is designed for interior, vertical use only. Acrylic will expand and contract with different temperatures level's and will perform best in temperature controlled environments with 1mm recommended expansion gaps.

Avoid use in areas exposed to intense direct sunlight such as adjacent to skylights or large un-shaded window. Acrylic is translucent in nature and should be used on plain side of calibrated surface with suitable adhesives.

Hot Machine press is not recommended for this product if processed in factories.

Applications:

Acrylic sheets can be laminated to a variety of substrates. Best results will be achieved using suitable adhesive or any other equivalent adhesive applied through automated lamination machine or a well controlled manual fashion. The combination of a very rigid substrate, such as High Density Fiber Board (HDF) or calibrated hardwood plywood with an adequate backing material is essential to achieve a stable panel.

Installation:

The installation of these sheets can be pasted with acrylic compactable adhesives on a calibrated clean and dust free dry surface. Use of laminate bonding tapes also can be used for difficult areas.

Maintainence:

Acrylic is easy to clean using mild soap, warm water and a soft microfiber cloth. Strong chemicals are not required. Minor scratching and scuffing can be easily removed by hand with selected liquid polices and a micro fibre cloth.



Certified and tested product | Better scratch resistance 100% Acrylic | Long lasting | HD colours



ACRILICO



